



	SPECIFICATION	TEST METHOD
Shelf Life	1 year	
Finish	Gloss	
Product Thickness	8 Mil	Micrometer
Weathering	>1%	ASTM D7869
Gravelometer	Pass	ASTM D3170
Elongation	190%	ASTM D412
Peel Strength	1700 gf/in	ASTM D3330

ROLL SIZES	24" x 50'	30" x 50'	36" x 50'	60" x 50'	72" x 50'
	24" x 1'	30" x 1'	36" x 1'	60" x 1'	72" x 1'
Satin only available in 60" Minimum order of 3', then 1'					

WARRANTY	12 YEARS*
----------	-----------

*Please refer to the warranty card for complete coverage and limitations.

NOTES	Liner: Silicone-coated PET Liner Adhesive: Solvent-based
-------	---

Disclaimer: All data provided in this document is based upon tests executed by CheetahWrap or their manufacturing partners and determined to be reliable information. Results may represent an average and any minimum or maximum values provided should be considered as a recommendation based on average circumstances. In the end, it is up to the end user to determine at their risk if the product is right for the desired application and outcome. These settings do not provide or imply a guarantee of the products use, outdoor durability, removability, or printability. As with most cast wrap films, this product is intended for and warranted for use with OEM paint that is less than 5 years old. Product should be stored upright in a temperature controlled environment. This information is subject to change at any time without notice.

